


SUGGESTED FIXING CENTRES
FOR M3 SCREW = 56.0



HOLE DETAIL
SCALE 2:1

TX0015 SPECIFICATION

AUDIO LINE LEVEL TRANSFORMER

URNS RATIO 1:1.

ISOLATION >500V BETWEEN PRIMARY & SECONDARY.

TO OPERATE WITH A PRIMARY SOURCE IMPEDANCE OF 50 OHMS.

SECONDARY LOAD IMPEDANCE OF 600 OHMS TO ∞ .

FREQUENCY RESPONSE 25 Hz TO 20 KHz ± 2 dB - AT ALL OUTPUT LEVELS & LOADS.

MAXIMUM OUTPUT @ 25 Hz + 22 dBm DISTORTION < 0.2%.

DISTORTION TYPICALLY < 0.05% 50 Hz - 20 KHz. AT ALL OUTPUT LEVELS & LOADS.

TERMINATION 300 mm FLYING LEADS OF 16/0.2 CABLE.

NOTES:- ALL DIMS IN MM
DO NOT SCALE.
TO HAVE NO BURRS OR EDGES
3RD ANGLE PROTECTION.
MOUNTING SURFACES AND FIXING HOLES
TO BE LEFT CLEAN AND FREE FROM
VARNISH

TITLE: BALANCING
TRANSFORMER
DETAILS.

PRODUCT: 'M' SERIES MIXER

B10419/01

AS DRAWN

Qty. 25-50 pcs

